



Corporate Memory Control (cmemc)

v22.1.1

Manual

Contents

1	Introduction	5
1.1	About eccenca Corporate Memory Control (cmemc)	5
1.2	Scope of delivery	6
2	Installation	7
2.1	Installation via pip	7
2.2	Installation via release package	7
2.2.1	Linux / MacOS installation	7
2.2.2	Windows installation	8
3	Configuration	9
4	Reference	12
4.1	Command group: admin	12
4.1.1	Command: admin showcase	12
4.1.2	Command: admin bootstrap	13
4.1.3	Command: admin status	13
4.1.4	Command: admin token	14
4.2	Command group: admin metrics	14
4.2.1	Command: admin metrics get	15
4.2.2	Command: admin metrics inspect	16
4.2.3	Command: admin metrics list	16
4.3	Command group: admin workspace	17
4.3.1	Command: admin workspace export	17
4.3.2	Command: admin workspace import	18
4.3.3	Command: admin workspace reload	18
4.4	Command group: admin workspace python	18
4.4.1	Command: admin workspace python install	19
4.4.2	Command: admin workspace python uninstall	19
4.4.3	Command: admin workspace python list	19
4.4.4	Command: admin workspace python list-plugins	20
4.5	Command group: admin store	20
4.5.1	Command: admin store showcase	21
4.5.2	Command: admin store bootstrap	21
4.5.3	Command: admin store export	22
4.5.4	Command: admin store import	22

4.6	Command group: config	22
4.6.1	Command: config list	24
4.6.2	Command: config edit	24
4.6.3	Command: config get	25
4.6.4	Command: config eval	25
4.7	Command group: dataset	26
4.7.1	Command: dataset list	26
4.7.2	Command: dataset delete	27
4.7.3	Command: dataset download	27
4.7.4	Command: dataset upload	28
4.7.5	Command: dataset inspect	28
4.7.6	Command: dataset create	29
4.7.7	Command: dataset open	30
4.8	Command group: dataset resource	30
4.8.1	Command: dataset resource list	30
4.8.2	Command: dataset resource delete	31
4.8.3	Command: dataset resource inspect	31
4.8.4	Command: dataset resource usage	32
4.9	Command group: graph	32
4.9.1	Command: graph count	32
4.9.2	Command: graph tree	33
4.9.3	Command: graph list	33
4.9.4	Command: graph export	34
4.9.5	Command: graph delete	35
4.9.6	Command: graph import	35
4.9.7	Command: graph open	36
4.10	Command group: project	36
4.10.1	Command: project open	36
4.10.2	Command: project list	37
4.10.3	Command: project export	37
4.10.4	Command: project import	38
4.10.5	Command: project delete	39
4.10.6	Command: project create	39
4.11	Command group: query	39
4.11.1	Command: query execute	40
4.11.2	Command: query list	41
4.11.3	Command: query open	42
4.11.4	Command: query status	42
4.11.5	Command: query replay	43
4.12	Command group: vocabulary	44
4.12.1	Command: vocabulary open	44
4.12.2	Command: vocabulary list	45
4.12.3	Command: vocabulary install	45
4.12.4	Command: vocabulary uninstall	45

4.12.5 Command: vocabulary import	46
4.13 Command group: vocabulary cache	46
4.13.1 Command: vocabulary cache update	47
4.13.2 Command: vocabulary cache list	47
4.14 Command group: workflow	47
4.14.1 Command: workflow execute	48
4.14.2 Command: workflow io	48
4.14.3 Command: workflow list	49
4.14.4 Command: workflow status	50
4.14.5 Command: workflow open	50
4.15 Command group: workflow scheduler	51
4.15.1 Command: workflow scheduler open	51
4.15.2 Command: workflow scheduler list	51
4.15.3 Command: workflow scheduler inspect	52
4.15.4 Command: workflow scheduler disable	52
4.15.5 Command: workflow scheduler enable	52

1 Introduction

This manual describes, how to install, setup and use *eccenca Corporate Memory Control* (cmemc), the command line client for eccenca Corporate Memory. cmemc is intended for system administrators and Linked Data Expert, who wants to automate and remote control activities on Corporate Memory.

To use this manual, cmemc users should have basic knowledge on command line interfaces, terminal usage and config file creation and editing.

This system manual includes the following parts:

- Installation
- Configuration

This document covers installation and basic usage pattern of cmemc and is not intended to be complete in terms of being a reference for all available options and commands. However, cmemc provides detailed documentation for users via the `--help` option.

The main documentation resource for cmemc is <https://eccenca.com/go/cmemc>.

1.1 About eccenca Corporate Memory Control (cmemc)

cmemc is the eccenca Corporate Memory Command Line Interface (CLI). It is developed in python and build and delivered as an open source python package.

Main features of cmemc include:

- List, edit and check configurations.
- List, create, delete, inspect datasets as well as dataset resources.
- List, import, export, delete or open graphs.
- List, import, export, create or delete Build projects.
- List, execute, replay or open local and remote SPARQL queries.
- List, install, uninstall, import and open vocabularies.
- List, execute, open or inspect workflows and workflow schedulers.
- Import or export whole Build workspaces and graph stores.
- List, get or inspect server metrics.

1.2 Scope of delivery

The cmemc release package consists of the following files:

- `cmem_cmemc-vXX.YY.tar.gz` - the source package of cmemc
- `cmem_cmempy-vXX.YY.tar.gz` - the source package of cmempy (the used python API to access Corporate Memory)
- `cmemc_vXX.YY_Manual.pdf` - the cmemc documentation manual (this document)
- `cmemc_vXX.YY_Manual.ttl` - the cmemc documentation as structured data (RDF graph)
- `requirements.txt` - additional requirements needed by cmemc

2 Installation

cmemc can be installed using the python sources, using the release package or using the docker image.

2.1 Installation via pip

cmemc is available as an [official pypi package](#)¹, so installation can be done with pip or pipx²:

```
$ pip install cmem-cmemc
```

```
$ pipx install cmem-cmemc
```

2.2 Installation via release package

2.2.1 Linux / MacOS installation

The cmemc distribution in the release package consists of source package which can be installed with pip as well.

The following script demonstrates how to install cmemc from these files:

```
$ pip install -r requirements.txt
...
$ pip install cmem_cmempy-v22.1.tar.gz
...
$ pip install cmem_cmemc-v22.1.tar.gz
```

Finally, test your installation.

```
$ cmemc --version
cmemc, version 22.1
```

¹<https://pypi.org/project/cmem-cmemc/>

²<https://pypa.github.io/pipx/>

In case you are using bash or zsh as your shell, you should enable tab completion for cmemc. This is documented on the [click framework homepage](#)³.

In order to enable tab completion with **bash** run the following command in your shell:

```
eval "$(_CMEMC_COMPLETE=source cmemc)"
```

In order to enable tab completion with **zsh** run the following command in your shell:

```
eval "$(_CMEMC_COMPLETE=source_zsh cmemc)"
```

You may want to add the corresponding line to your `.bashrc` or `.zshrc` in order to enable completion per default.

2.2.2 Windows installation

The installation for Windows is similar once you have installed python from the store.

³<https://click.palletsprojects.com/en/7.x/bashcomplete/#activation>

3 Configuration

cmemc needs to know where your Corporate Memory is deployed. For this, you need to provide some key variables in a configuration file. Per default, cmemc looks for this configuration file on a reasonable place depending on your operating system.

For Linux, this is `$HOME/.config/cmemc/config.ini`.

For Windows, this is `%APPDATA%\cmemc\config.ini`

Note: `USER` is your actual user name.

Once you start cmemc the first time, it will create an empty config file at this location and will output a general introduction. In order to do so, open the terminal application of your choice.

Note: All further examples given here are based on Linux commands. For Windows, the output is the same, however, you need to start cmemc as `cmemc.exe`.

```
$ cmemc
Empty config created: /home/user/.config/cmemc/config.ini
Usage: cmemc [OPTIONS] COMMAND [ARGS]...

eccenca Corporate Memory Control (cmemc).
```

cmemc is the eccenca Corporate Memory Command Line Interface (CLI).

Available commands are grouped by affecting resource **type** (such as graph, project and query). Each **command** and group has a separate `--help` screen **for** detailed documentation. In order to see possible commands **in** a group, simply execute the group **command** without further parameter (e.g. `cmemc project`).

If your terminal supports colors, these coloring rules are applied: Groups are colored **in** white; Commands which change data are colored **in** red; all other commands as well as options are colored **in** green.

Please also have a look at the cmemc online documentation:

<https://eccenca.com/go/cmemc>

```
cmemc is © 2022 eccenca GmbH, licensed under the Apache License 2.0.
```

Options:

```
-c, --connection TEXT  Use a specific connection from the config file.  
--config-file FILE    Use this config file instead of the default one.  
                      [default: /Users/seebi/Library/Application  
                       Support/cmemc/config.ini]  
  
-q, --quiet           Suppress any non-error info messages.  
-d, --debug           Output debug messages and stack traces after errors.  
--version            Show the version and exit.  
-h, --help             Show this message and exit.
```

Commands:

```
admin      Import bootstrap data, backup/restore workspace or get status.  
config     List and edit configs as well as get config values.  
dataset    List, create, delete, inspect, up-/download or open datasets.  
graph      List, import, export, delete, count, tree or open graphs.  
project    List, import, export, create, delete or open projects.  
query      List, execute, get status or open SPARQL queries.  
vocabulary List, (un-)install, import or open vocabs / manage cache.  
workflow   List, execute, status or open (io) workflows.
```

You should now edit your config file and add credentials and URL parameter of your Corporate Memory deployment. You either search for the config file manually in your home directory, or you can use the `config edit` command, which opens the config file in your default text editor.

```
$ cmemc config edit  
Open editor for config file /home/user/.config/cmemc/config.ini
```

The rules for the config file are similar to a Windows INI file and are explained in detail at [docs.python.org¹](https://docs.python.org/3/library/configparser.html). Here is a basic example:

```
[my-local]  
CMEM_BASE_URI=http://localhost/  
OAUTH_GRANT_TYPE=client_credentials  
OAUTH_CLIENT_ID=cmem-service-account  
OAUTH_CLIENT_SECRET=c9c12831-000c-464b-9b1d-2d8b7e20df6a
```

This basically creates a named section `my-local` which is a connection to a Corporate Memory deployment on `http://localhost`. The authorization will be done with a system account `cmem-service-`

¹<https://docs.python.org/3/library/configparser.html>

`account` and the given client secret. Using this combination of config parameter is based on a typical installation where all components are available under the same hostname.

However, if you need to fine tune all locations, the following config file parameter can be used in addition to this example:

- `DI_API_ENDPOINT` - Data Integration API endpoint, default: `CMEM_BASE_URI/dataintegration`
- `DP_API_ENDPOINT` - Data Platform API endpoint, default: `CMEM_BASE_URI/dataplatform`
- `OAUTH_TOKEN_URI` - OAuth 2.0 Token endpoint, default: `CMEM_BASE_URI/auth/realms/cmcm/protocol/openid-connect/token`
- `OAUTH_GRANT_TYPE` - OAuth 2.0 grant type, default: `client_credentials`
- `OAUTH_USER` - Username to retrieve the token, default: `admin`, only if `OAUTH_GRANT_TYPE` is `password`
- `OAUTH_PASSWORD` - Password to retrieve the token, default: `admin`, only if `OAUTH_GRANT_TYPE` is `password`
- `OAUTH_CLIENT_ID` - OAuth 2.0 client id, default: `cmem-service-account`
- `OAUTH_CLIENT_SECRET` - OAuth 2.0 client secret, default: `secret`, only if `OAUTH_GRANT_TYPE` is `client_credentials`
- `SSL_VERIFY` - Use SSL verification for requests to DP/DI default: `True`
- `OAUTH_AUTH_TOKEN` - a pre-fetched auth token, only if `OAUTH_GRANT_TYPE` is `prefetched_token`

In order to verify your configuration, you should try to get a list of graphs via cmemc:

```
$ cmemc -c my-local graph list
```

Graph IRI	Type	Label
<code>urn:elds-backend-access-conditions-graph</code>	<code>void:Dataset</code>	CMEM Access Conditions
<code>https://ns.eccenca.com/data/config/</code>	<code>void:Dataset</code>	CMEM Configuration
<code>https://ns.eccenca.com/data/queries/</code>	<code>void:Dataset</code>	CMEM Query Catalog
<code>https://vocab.eccenca.com/shacl/</code>	<code>void:Dataset</code>	CMEM Shapes Catalog
<code>https://ns.eccenca.com/example/data/vocabs/</code>	<code>void:Dataset</code>	CMEM Vocabulary Catalog

If you get a similar list of graphs, you successfully configured cmemc to access your deployment.

4 Reference

This section lists the help texts of all commands as a reference and to search for it.

4.1 Command group: admin

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

Import bootstrap data, backup/restore workspace or get status.

This command group consists of commands for setting up and configuring eccenca Corporate Memory.

Options:

-h, --help Show this message and exit.

Commands:

bootstrap	Update/Import bootstrap data.
metrics	List and get metrics.
showcase	Create showcase data.
status	Output health and version information.
store	Import, export and bootstrap the knowledge graph store.
token	Fetch and output an access token.
workspace	Import, export and reload the project workspace.

4.1.1 Command: admin showcase

```
Usage: cmemc [OPTIONS]
```

Create showcase data.

This command creates a showcase scenario of multiple graphs including integration graphs, shapes, statement annotations etc.

Note: There is currently no deletion mechanism for the showcase data, so you need to remove the showcase graphs manually (or just remove all graphs).

Options:

```
--scale INTEGER The scale factor provides a way to set the target size of  
the scenario. A value of 10 results in around 40k triples,  
a value of 50 in around 350k triples. [default: 10]  
  
--create Delete old showcase data if present and create new showcase  
databased on the given scale factor.  
  
--delete Delete existing showcase data if present.  
-h, --help Show this message and exit.
```

4.1.2 Command: admin bootstrap

Usage: cmemc [OPTIONS]

Update/Import bootstrap data.

This command imports the bootstrap data needed for managing shapes, access conditions, the query catalog and the vocabulary catalog.

Note: There is currently no deletion mechanism for the bootstrap data, so you need to remove the graphs manually (or just remove all graphs).

Options:

```
--import Delete existing bootstrap data if present and import bootstrap  
data which was delivered  
  
-h, --help Show this message and exit.
```

4.1.3 Command: admin status

Usage: cmemc [OPTIONS]

Output health and version information.

This command outputs version and health information of the selected deployment. If the version information can not be retrieved, UNKNOWN is shown if the endpoint is not available or ERROR is shown, if the endpoints returns an error.

In addition to that, this command warns you if the target version of your

```
cmemc client is newer than the version of your backend and if the  
ShapeCatalog has a different version then your DataPlatform component.
```

To get status information of all configured deployments use this command
in combination with parallel:

```
cmemc config list | parallel --ctag cmemc -c {} admin status
```

Options:

```
-h, --help Show this message and exit.
```

4.1.4 Command: admin token

```
Usage: cmemc [OPTIONS]
```

Fetch and output an access token.

This command can be used to check for correct authentication as well as to
use the token with wget / curl or similar standard tools:

```
Example Usage: curl -H "Authorization: Bearer $(cmemc -c my admin token)"  
$(cmemc -c my config get DP_API_ENDPOINT)/api/custom/slug
```

Please be aware that this command can reveal secrets, which you do not
want to have in log files or on the screen.

Options:

```
--raw      Outputs raw JSON. Note that this option will always try to fetch  
           a new JSON token response. In case you are working with  
           OAUTH_GRANT_TYPE=prefetched_token, this may lead to an error.
```

```
--decode   Decode the access token and outputs the raw JSON. Note that the  
           access token is only decoded and esp. not validated.
```

```
-h, --help Show this message and exit.
```

4.2 Command group: admin metrics

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List and get metrics.

This command group consists of commands for reading and listing internal monitoring metrics of eccenca Corporate Memory. A deployment consists of multiple jobs (e.g. DP, DI), which provide multiple metric families on an endpoint.

Each metric family can consist of different samples identified by labels with a name and a value (dimensions). A metric has a specific type (counter, gauge, summary and histogram) and additional metadata.

Please have a look at https://prometheus.io/docs/concepts/data_model/ for further details.

Options:

-h, --help Show this message and exit.

Commands:

get Get sample data of a metric.
inspect Inspect a metric.
list List metrics for a specific job.

4.2.1 Command: admin metrics get

Usage: cmemc [OPTIONS] METRIC_ID

Get sample data of a metric.

A metric of a specific job is identified by a metric ID. Possible metric IDs of a job can be retrieved with the `metrics list` command. A metric can contain multiple samples. These samples are distinguished by labels (name and value).

Options:

--job [DP] The job from which the metrics data is fetched.
[default: DP]

--filter <TEXT TEXT>... A set of label name/value pairs in order to filter the samples of the requested metric family. Each metric has a different set of labels with different values. In order to get a list of possible label names and values, use the command without this option. The label names are then shown as column headers and label values as cell values of this column.

```
--enforce-table      A single sample value will be returned as plain
                     text instead of the normal table. This allows for
                     more easy integration with scripts. This flag
                     enforces the use of tabular output, even for single
                     row tables.

--raw               Outputs raw prometheus sample classes.

-h, --help           Show this message and exit.
```

4.2.2 Command: admin metrics inspect

```
Usage: cmemc [OPTIONS] METRIC_ID
```

Inspect a metric.

This command outputs the data of a metric. The first table includes basic meta data about the metric. The second table includes sample labels and values.

Options:

```
--job [DP]  The job from which the metrics data is fetched. [default: DP]
--raw       Outputs raw JSON of the table data.
-h, --help   Show this message and exit.
```

4.2.3 Command: admin metrics list

```
Usage: cmemc [OPTIONS]
```

List metrics for a specific job.

For each metric, the output table shows the metric ID, the type of the metric, a count of how many labels (label names) are describing the samples (L) and a count of how many samples are currently available for a metric (S).

Options:

```
--job [DP]  The job from which the metrics data is fetched. [default: DP]
--id-only   Lists metric identifier only. This is useful for piping the IDs
            into other commands.

--raw       Outputs (sorted) JSON dict, parsed from the metrics API output.
```

```
-h, --help Show this message and exit.
```

4.3 Command group: admin workspace

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

```
Import, export and reload the project workspace.
```

```
Options:
```

```
-h, --help Show this message and exit.
```

```
Commands:
```

```
export Export the complete workspace (all projects) to a ZIP file.
```

```
import Import the workspace from a file.
```

```
python List, install, or uninstall python packages.
```

```
reload Reload the workspace from the backend.
```

4.3.1 Command: admin workspace export

```
Usage: cmemc [OPTIONS] [FILE]
```

```
Export the complete workspace (all projects) to a ZIP file.
```

```
Depending on the requested type, this ZIP contains either a turtle file  
for each project (type rdfTurtle) or a substructure of resource files and  
XML descriptions (type xmlZip).
```

```
The file name is optional and will be generated with by the template if  
absent.
```

```
Options:
```

```
-o, --overwrite Overwrite existing files. This is a dangerous  
option, so use it with care.
```

```
--type TEXT Type of the exported workspace file.  
[default: xmlZip]
```

```
-t, --filename-template TEXT Template for the export file name. Possible  
placeholders are (Jinja2): {{connection}}  
(from the --connection option) and {{date}}  
(the current date as YYYY-MM-DD). The file  
suffix will be appended. Needed directories
```

```
will be created. [default:  
{{date}}-{{connection}}.workspace]
```

```
-h, --help Show this message and exit.
```

4.3.2 Command: admin workspace import

```
Usage: cmemc [OPTIONS] FILE
```

Import the workspace from a file.

Options:

```
--type TEXT Type of the exported workspace file. [default: xmlZip]  
-h, --help Show this message and exit.
```

4.3.3 Command: admin workspace reload

```
Usage: cmemc [OPTIONS]
```

Reload the workspace from the backend.

Options:

```
-h, --help Show this message and exit.
```

4.4 Command group: admin workspace python

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List, install, or uninstall python packages.

Python packages are used to extend the DataIntegration workspace with python plugins. To get a list of installed packages, execute the list command.

Warning: Installing packages from unknown sources is not recommended.
Plugins are not verified for malicious code.

Options:

```
-h, --help Show this message and exit.
```

Commands:

```
install      Install a python package to the workspace.  
list        List installed python packages.  
list-plugins List installed workspace plugins.  
uninstall    Uninstall a python package from the workspace.
```

4.4.1 Command: admin workspace python install

Usage: cmemc [OPTIONS] PACKAGE

Install a python package to the workspace.

This command is basically a 'pip install' in the remote python environment.

You can install a package by uploading a source distribution .tar.gz file, or by uploading a build distribution .whl file, or by specifying a package name, more precisely, a pip requirement specifier with a package name available on pypi.org (e.g. 'requests==2.27.1').

Options:

-h, --help Show this message and exit.

4.4.2 Command: admin workspace python uninstall

Usage: cmemc [OPTIONS] PACKAGE_NAME

Uninstall a python package from the workspace.

This command is basically a 'pip uninstall' in the remote python environment.

Options:

-h, --help Show this message and exit.

4.4.3 Command: admin workspace python list

Usage: cmemc [OPTIONS]

List installed python packages.

This command is basically a 'pip list' in the remote python environment.

It outputs a table of python package identifiers with version information.

Options:

- raw Outputs raw JSON.
 - id-only Lists only package identifier. This is useful for piping the IDs into other commands.
- h, --help Show this message and exit.

4.4.4 Command: admin workspace python list-plugins

Usage: cmemc [OPTIONS]

List installed workspace plugins.

This command lists all discovered plugins. Note that the plugin discovery is limited to specific packages.

Options:

- raw Outputs raw JSON.
 - id-only Lists only plugin identifier.
- h, --help Show this message and exit.

4.5 Command group: admin store

Usage: cmemc [OPTIONS] COMMAND [ARGS]...

Import, export and bootstrap the knowledge graph store.

This command group consist of commands to administrate the knowledge graph store as a whole.

Options:

- h, --help Show this message and exit.

Commands:

- bootstrap Update/Import bootstrap data.
- export Backup all knowledge graphs to a ZIP archive.
- import Restore graphs from a ZIP archive.
- showcase Create showcase data.

4.5.1 Command: admin store showcase

```
Usage: cmemc [OPTIONS]
```

Create showcase data.

This command creates a showcase scenario of multiple graphs including integration graphs, shapes, statement annotations etc.

Note: There is currently no deletion mechanism for the showcase data, so you need to remove the showcase graphs manually (or just remove all graphs).

Options:

--scale INTEGER The scale factor provides a way to set the target size of the scenario. A value of 10 results in around 40k triples, a value of 50 in around 350k triples. [default: 10]

--create Delete old showcase data if present and create new showcase databased on the given scale factor.

--delete Delete existing showcase data if present.

-h, --help Show this message and exit.

4.5.2 Command: admin store bootstrap

```
Usage: cmemc [OPTIONS]
```

Update/Import bootstrap data.

This command imports the bootstrap data needed for managing shapes, access conditions, the query catalog and the vocabulary catalog.

Note: There is currently no deletion mechanism for the bootstrap data, so you need to remove the graphs manually (or just remove all graphs).

Options:

--import Delete existing bootstrap data if present and import bootstrap data which was delivered

-h, --help Show this message and exit.

4.5.3 Command: admin store export

```
Usage: cmemc [OPTIONS] BACKUP_FILE
```

Backup all knowledge graphs to a ZIP archive.

The backup file is a ZIP archive containing all knowledge graphs as Turtle files + configuration file for each graph.

This command will create lots of load on the server. It can take a long time to complete.

Options:

```
--overwrite Overwrite existing files. This is a dangerous option, so use it with care.
```

```
-h, --help Show this message and exit.
```

4.5.4 Command: admin store import

```
Usage: cmemc [OPTIONS] BACKUP_FILE
```

Restore graphs from a ZIP archive.

The backup file is a ZIP archive containing all knowledge graphs as Turtle files + configuration file for each graph.

The command will load a single backup ZIP archive into the triple store, by replacing all graphs with the content of the Turtle files in the archive and deleting all graphs which are not in the archive.

This command will create lots of load on the server. It can take a long time to complete. The backup file will be transferred to the server, then unzipped and imported graph by graph. After the initial transfer, the network connection is not used anymore, so it will be closed by proxies sometimes. This does not mean that the import failed.

Options:

```
-h, --help Show this message and exit.
```

4.6 Command group: config

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List and edit configs as well as get config values.

Configurations are identified by the section identifier in the config file. Each configuration represent a Corporate Memory deployment with its specific access method as well as credentials.

A minimal configuration which uses client credentials has the following entries:

```
[example.org]
CMEM_BASE_URI=https://cmem.example.org/
OAUTH_GRANT_TYPE=client_credentials
OAUTH_CLIENT_ID=cmem-service-account
OAUTH_CLIENT_SECRET=my-secret-account-pass
```

Note that OAUTH_GRANT_TYPE can be either client_credentials, password or prefetched_token.

In addition to that, the following config parameters can be used as well:

```
SSL_VERIFY=False      - for ignoring certificate issues (not recommended)
DP_API_ENDPOINT=URL - to point to a non-standard DataPlatform location
DI_API_ENDPOINT=URL - to point to a non-standard DataIntegration location
OAUTH_TOKEN_URI=URL - to point to an external IdentityProvider location
OAUTH_USER=username - only if OAUTH_GRANT_TYPE=password
OAUTH_PASSWORD=password - only if OAUTH_GRANT_TYPE=password
OAUTH_ACCESS_TOKEN=token - only if OAUTH_GRANT_TYPE=prefetched_token
```

In order to get credential information from an external process, you can use the parameter OAUTH_PASSWORD_PROCESS, OAUTH_CLIENT_SECRET_PROCESS and OAUTH_ACCESS_TOKEN_PROCESS to setup an external executable.

```
OAUTH_CLIENT_SECRET_PROCESS=/path/to/getpass.sh
OAUTH_PASSWORD_PROCESS=["getpass.sh", "parameter1", "parameter2"]
```

The credential executable can use the cmemc environment for fetching the credential (e.g. CMEM_BASE_URI and OAUTH_USER). If the credential executable is not given with a full path, cmemc will look into your environment PATH for something which can be executed. The configured process needs to return the credential on the first line of stdout. In addition to that, the process needs to exit with exit code 0 (without

failure). There are examples available in the online manual.

Options:

-h, --help Show this message and exit.

Commands:

edit Edit the user-scope configuration file.

eval Export all configuration values of a configuration for evaluation.

get Get the value of a known cmemc configuration key.

list List configured connections.

4.6.1 Command: config list

Usage: cmemc [OPTIONS]

List configured connections.

This command lists all configured connections from the currently used config file.

The connection identifier can be used with the --connection option in order to use a specific Corporate Memory instance.

In order to apply commands on more than one instance, you need to use typical unix gear such as xargs or parallel:

```
cmemc config list | xargs -I % sh -c 'cmemc -c % admin status'
```

```
cmemc config list | parallel --jobs 5 cmemc -c {} admin status
```

Options:

-h, --help Show this message and exit.

4.6.2 Command: config edit

Usage: cmemc [OPTIONS]

Edit the user-scope configuration file.

Options:

-h, --help Show this message and exit.

4.6.3 Command: config get

```
Usage: cmemc [OPTIONS] [CMEM_BASE_URI|SSL_VERIFY|REQUESTS_CA_BUNDLE|DP_API_END  
POINT|DI_API_ENDPOINT|OAUTH_TOKEN_URI|OAUTH_GRANT_TYPE|OAUTH_USER  
|OAUTH_PASSWORD|OAUTH_CLIENT_ID|OAUTH_CLIENT_SECRET|OAUTH_ACCESS_  
TOKEN]
```

Get the value of a known cmemc configuration key.

In order to automate processes such as fetching custom API data from multiple Corporate Memory instances, this command provides a way to get the value of a cmemc configuration key for the selected deployment.

```
Example Usage: curl -H "Authorization: Bearer $(cmemc -c my admin token)"  
$(cmemc -c my config get DP_API_ENDPOINT)/api/custom/slug
```

The commands returns with exit code 1 if the config key is not used in the current configuration.

Options:

```
-h, --help Show this message and exit.
```

4.6.4 Command: config eval

```
Usage: cmemc [OPTIONS]
```

Export all configuration values of a configuration for evaluation.

The output of this command is suitable to be used by a shells eval command. It will output the complete configuration as 'export key="value"' statements. This allows for preparation of a shell environment.

```
eval $(cmemc -c my config eval)
```

Please be aware that credential details are shown in cleartext with this command.

Options:

```
--unset Instead of export all configuration keys, this option will unset  
all key.
```

```
-h, --help Show this message and exit.
```

4.7 Command group: dataset

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List, create, delete, inspect, up-/download or open datasets.

This command group allows for managing workspace datasets as well as dataset file resources. Datasets can be created and deleted. File resources can be uploaded and downloaded. Details of dataset parameter can be listed with inspect.

Datasets are identified with a combined key of the project ID and the project internal dataset ID (e.g: my-project:my-dataset). To get a list of datasets, use the list command.

Options:

-h, --help Show this message and exit.

Commands:

create	Create a dataset.
delete	Delete datasets.
download	Download the resource file of a dataset.
inspect	Display meta data of a dataset.
list	List available datasets.
open	Open datasets in the browser.
resource	List, inspect or delete dataset file resources.
upload	Upload a resource file to a dataset.

4.7.1 Command: dataset list

```
Usage: cmemc [OPTIONS]
```

List available datasets.

Outputs a list of datasets IDs which can be used as reference for the dataset create and delete commands.

Options:

--project TEXT	The project, from which you want to list the datasets. Project IDs can be listed with the 'project list' command.
--raw	Outputs raw JSON objects of dataset search API response.
--id-only	Lists only dataset identifier and no labels or other meta

```
data. This is useful for piping the ids into other cmemc commands.
```

```
-h, --help      Show this message and exit.
```

4.7.2 Command: dataset delete

```
Usage: cmemc [OPTIONS] [DATASET_IDS]...
```

Delete datasets.

This deletes existing datasets in integration projects from Corporate Memory. Datasets will be deleted without prompting! Dataset resources will not be deleted.

Example: cmemc dataset delete my_project:my_dataset

Datasets can be listed by using the 'cmemc dataset list' command.

Options:

```
-a, --all      Delete all datasets. This is a dangerous option, so use it with care.
```

```
--project TEXT In combination with the '--all' flag, this option allows for deletion of all datasets of a certain project. The behaviour is similar to the 'dataset list --project' command.
```

```
-h, --help      Show this message and exit.
```

4.7.3 Command: dataset download

```
Usage: cmemc [OPTIONS] DATASET_ID OUTPUT_PATH
```

Download the resource file of a dataset.

This command downloads the file resource of a dataset to your local file system or to standard out (-). Note that this is not possible for dataset types such as Knowledge Graph (eccencaDataplatform) or SQL endpoint (sqlEndpoint).

Without providing an output path, the output file name will be the same as the remote file resource.

Datasets can be listed by using the 'cmemc dataset list' command.

Options:

- replace Replace existing files. This is a dangerous option, so use it with care.
- h, --help Show this message and exit.

4.7.4 Command: dataset upload

Usage: cmemc [OPTIONS] DATASET_ID INPUT_PATH

Upload a resource file to a dataset.

This command uploads a file to a dataset. The content of the uploaded file replaces the remote file resource. The name of the remote file resource is not changed.

Warning: If the remote file resource is used in more than one dataset, the other datasets are also affected by this command.

Warning: The content of the uploaded file is not tested, so uploading a json file to an xml dataset will result in errors.

Datasets can be listed by using the 'cmemc dataset list' command.

Example: cmemc dataset upload cmem:my-dataset new-file.csv

Options:

- h, --help Show this message and exit.

4.7.5 Command: dataset inspect

Usage: cmemc [OPTIONS] DATASET_ID

Display meta data of a dataset.

Options:

- raw Outputs raw JSON.
- h, --help Show this message and exit.

4.7.6 Command: dataset create

```
Usage: cmemc [OPTIONS] [DATASET_FILE]
```

Create a dataset.

Datasets are created in projects and can have associated file resources. Each dataset has a type (such as 'csv') and a list of parameter which can change or specify the dataset behaviour.

To get more information on possible dataset types and parameter on these types, use the '--help-types' and '--help-parameter' options.

Example: cmemc dataset create --project my-project --type csv my-file.csv

Options:

-t, --type TEXT	The dataset type of the dataset to create. Example types are 'csv', 'json' and 'eccencaDataPlatform' (-> Knowledge Graph).
--project TEXT	The project, where you want to create the dataset in. If there is only one project in the workspace, this option can be omitted.
-p, --parameter <TEXT TEXT>...	A set of key/value pairs. Each dataset type has different parameters (such as charset, arraySeparator, ignoreBadLines, ...). In order to get a list of possible parameter, use the '--help-parameter' option.
--replace	Replace remote file resources in case there already exists a file with the same name.
--id TEXT	The dataset ID of the dataset to create. The dataset ID will be automatically created in case it is not present.
--help-types	Lists all possible dataset types on given Corporate Memory instance. Note that this option already needs access to the instance.
--help-parameter	Lists all possible (optional and mandatory) parameter for a dataset type. Note that this option already needs access to the instance.

-h, --help Show this message and exit.

4.7.7 Command: dataset open

Usage: cmemc [OPTIONS] DATASET_IDS...

Open datasets in the browser.

With this command, you can open a dataset in the workspace in your browser.

The command accepts multiple dataset IDs which results in opening multiple browser tabs.

Options:

-h, --help Show this message and exit.

4.8 Command group: dataset resource

Usage: cmemc [OPTIONS] COMMAND [ARGS]...

List, inspect or delete dataset file resources.

File resources are identified by its name and project ID.

Options:

-h, --help Show this message and exit.

Commands:

delete Delete file resources.
inspect Display all meta data of a file resource.
list List available file resources.
usage Display all usage data of a file resource.

4.8.1 Command: dataset resource list

Usage: cmemc [OPTIONS]

List available file resources.

```
Outputs a table or a list of dataset resources (files).
```

Options:

- raw Outputs raw JSON.
- id-only Lists only resource names and no other meta data.
This is useful for piping the IDs into other commands.
- filter <TEXT TEXT>... Filter file resources based on a meta data. First parameter CHOICE can be one of ['project', 'regex']. The second parameter is based on CHOICE, e.g. a project ID or a regular expression string.
- h, --help Show this message and exit.

4.8.2 Command: dataset resource delete

```
Usage: cmemc [OPTIONS] [RESOURCE_IDS]...
```

Delete file resources.

You have three selection mechanisms: with specific IDs, you will delete only these resources; by using --filter your will delete resources based on the filter type and value; by using --all will delete all resources.

Options:

- force Delete resource even if in use by a task.
- a, --all Delete all resources. This is a dangerous option, so use it with care.
- filter <TEXT TEXT>... Filter file resources based on a meta data. First parameter CHOICE can be one of ['project', 'regex']. The second parameter is based on CHOICE, e.g. a project ID or a regular expression string.
- h, --help Show this message and exit.

4.8.3 Command: dataset resource inspect

```
Usage: cmemc [OPTIONS] RESOURCE_ID
```

Display all meta data of a file resource.

```
Options:  
  --raw      Outputs raw JSON.  
  -h, --help Show this message and exit.
```

4.8.4 Command: dataset resource usage

```
Usage: cmemc [OPTIONS] RESOURCE_ID  
  
Display all usage data of a file resource.  
  
Options:  
  --raw      Outputs raw JSON.  
  -h, --help Show this message and exit.
```

4.9 Command group: graph

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...  
  
List, import, export, delete, count, tree or open graphs.  
  
Graphs are identified by an IRI. To get a list of existing graphs,  
execute the list command or use tab-completion.  
  
Options:  
  -h, --help Show this message and exit.  
  
Commands:  
  count   Count triples in graph(s).  
  delete  Delete graph(s) from the store.  
  export   Export graph(s) as NTriples to stdout (-), file or directory.  
  import   Import graph(s) to the store.  
  list    List accessible graphs.  
  open    Open / explore a graph in the browser.  
  tree    Show graph tree(s) of the owl:imports hierarchy.
```

4.9.1 Command: graph count

```
Usage: cmemc [OPTIONS] [IRIS]...  
  
Count triples in graph(s).
```

This command lists graphs with their triple count. Counts are done without following imported graphs.

Options:

- a, --all Count all graphs
- s, --summarize Display only a sum of all counted graphs together
- h, --help Show this message and exit.

4.9.2 Command: graph tree

Usage: cmemc [OPTIONS] [IRIS]...

Show graph tree(s) of the owl:imports hierarchy.

You can output one or more trees of the import hierarchy.

Imported graphs which do not exist are shown as [missing: IRI]. Imported graphs which will result in an import cycle are shown as [ignored: IRI]. Each graph is shown with label and IRI.

Options:

- a, --all Show tree of all (readable) graphs.
- raw Outputs raw JSON of the graph importTree API response.
- id-only Lists only graph identifier (IRIs) and no labels or other meta data. This is useful for piping the IRIs into other commands.
The output with this option is a sorted, flat, de-duplicated list of existing graphs.

-h, --help Show this message and exit.

4.9.3 Command: graph list

Usage: cmemc [OPTIONS]

List accessible graphs.

Options:

- raw Outputs raw JSON of the graphs list API response.
- id-only Lists only graph identifier (IRIs) and no labels or other meta data. This is useful for piping the IRIs into other commands.

```
--filter <CHOICE TEXT>... Filter graphs based on effective access  
conditions or import closure. First parameter  
CHOICE can be 'access' or 'imported-by'. The  
second parameter can be 'readonly' or 'writeable'  
in case of 'access' or any readable graph in case  
of 'imported-by'.
```

-h, --help	Show this message and exit.
------------	-----------------------------

4.9.4 Command: graph export

```
Usage: cmemc [OPTIONS] [IRIS]...
```

```
Export graph(s) as NTriples to stdout (-), file or directory.
```

```
In case of file export, data from all selected graphs will be concatenated  
in one file. In case of directory export, .graph and .ttl files will be  
created for each graph.
```

Options:

-a, --all	Export all readable graphs.
--include-imports	Export selected graph(s) and all graphs which are imported from these selected graph(s).
--create-catalog	In addition to the .ttl and .graph files, cmemc will create an XML catalog file (catalog-v001.xml) which can be used by applications such as Protégé.
--output-dir DIRECTORY	Export to this directory.
--output-file FILE	Export to this file. [default: -]
-t, --filename-template TEXT	Template for the export file name(s). Used together with --output-dir. Possible placeholders are (Jinja2): {{hash}} - sha256 hash of the graph IRI, {{iriname}} - graph IRI converted to filename, {{connection}} - from the --connection option and {{date}} - the current date as YYYY-MM-DD. The file suffix will be appended. Needed directories will be created. [default: {{hash}}]

```
--mime-type [application/n-triples|text/turtle]
          Define the requested mime type [default:
          application/n-triples]

-h, --help           Show this message and exit.
```

4.9.5 Command: graph delete

```
Usage: cmemc [OPTIONS] [IRIS]...

Delete graph(s) from the store.

Options:
-a, --all            Delete all writeable graphs.
--include-imports   Delete selected graph(s) and all writeable graphs which
                    are imported from these selected graph(s).

-h, --help           Show this message and exit.
```

4.9.6 Command: graph import

```
Usage: cmemc [OPTIONS] INPUT_PATH [IRI]

Import graph(s) to the store.

If input is an directory, it scans for file-pairs such as xxx.ttl and
xxx.ttl.graph where xxx.ttl is the actual triples file and xxx.ttl.graph
contains the graph IRI as one string: "https://mygraph.de/xxx/". If input
is a file, content will be uploaded to IRI. If --replace is set, the data
will be overwritten, if not, it will be added.

Options:
--replace           Replace / overwrite the graph - instead of just adding new
                   triples the graph.

--skip-existing    Skip importing a file if the target graph already exists in
                   the store. Note that the graph list is fetched once at the
                   beginning of the process, so that you can still add
                   multiple files to one single graph (if it does not exist).

-h, --help           Show this message and exit.
```

4.9.7 Command: graph open

```
Usage: cmemc [OPTIONS] IRI
```

Open / explore a graph in the browser.

Options:

```
-h, --help Show this message and exit.
```

4.10 Command group: project

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List, import, export, create, delete or open projects.

Projects are identified by an PROJECTID. To get a list of existing projects, execute the list command or use tab-completion.

Options:

```
-h, --help Show this message and exit.
```

Commands:

```
create  Create empty new project(s).  
delete  Delete project(s).  
export   Export project(s) to file(s).  
import   Import a project from a file or directory.  
list    List available projects.  
open    Open projects in the browser.
```

4.10.1 Command: project open

```
Usage: cmemc [OPTIONS] PROJECT_IDS...
```

Open projects in the browser.

With this command, you can open a project in the workspace in your browser to change them.

The command accepts multiple projects IDs which results in opening multiple browser tabs.

Options:

```
-h, --help Show this message and exit.
```

4.10.2 Command: project list

```
Usage: cmemc [OPTIONS]
```

List available projects.

Outputs a list of project IDs which can be used as reference for the project create, delete, export and import commands.

Options:

```
--raw      Outputs raw JSON.  
--id-only  Lists only project identifier and no labels or other meta data.  
           This is useful for piping the IDs into other commands.
```

```
-h, --help Show this message and exit.
```

4.10.3 Command: project export

```
Usage: cmemc [OPTIONS] [PROJECT_IDS]...
```

Export project(s) to file(s).

Projects can be exported with different export formats. The default type is a zip archive which includes meta data as well as dataset resources. If more than one project is exported, a file is created for each project. By default, these files are created in the current directory and with a descriptive name (see --template option default).

Example: cmemc project export my_project

Available projects can be listed by using the 'cmemc project list' command.

You can use the template string to create subdirectories as well: cmemc config list | parallel -I% cmemc -c % project export --all -t "dump/{{connection}}/{{date}}-{{id}}.project"

Options:

```
-a, --all          Export all projects.  
-o, --overwrite   Overwrite existing files. This is a dangerous
```

	option, so use it with care.
--output-dir DIRECTORY	The base directory, where the project files will be created. If this directory does not exist, it will be silently created. [default: .]
--type TEXT	Type of the exported project file(s). Use the --help-types option or tab completion to see a list of possible types. [default: xmlZip]
-t, --filename-template TEXT	Template for the export file name(s). Possible placeholders are (Jinja2): {{id}} (the project ID), {{connection}} (from the --connection option) and {{date}} (the current date as YYYY-MM-DD). The file suffix will be appended. Needed directories will be created. [default: {{date}}-{{connection}}-{{id}}.project]
--extract	Export projects to a directory structure instead of a ZIP archive. Note that the --filename-template option is ignored here. Instead, a sub-directory per exported project is created under the output directory. Also note that not all export types are extractable.
--help-types	Lists all possible export types.
-h, --help	Show this message and exit.

4.10.4 Command: project import

Usage: cmemc [OPTIONS] PATH PROJECT_ID

Import a project from a file or directory.

Example: cmemc project import my_project.zip my_project

Options:

-o, --overwrite Overwrite an existing project. This is a dangerous option, so use it with care.

-h, --help Show this message and exit.

4.10.5 Command: project delete

```
Usage: cmemc [OPTIONS] [PROJECT_IDS]...
```

Delete project(s).

This deletes existing data integration projects from Corporate Memory.
Projects will be deleted without prompting!

Example: cmemc project delete my_project

Projects can be listed by using the 'cmemc project list' command.

Options:

- a, --all Delete all projects. This is a dangerous option, so use it with care.
- h, --help Show this message and exit.

4.10.6 Command: project create

```
Usage: cmemc [OPTIONS] PROJECT_IDS...
```

Create empty new project(s).

This creates one or more new projects. Existing projects will not be overwritten.

Example: cmemc project create my_project

Projects can be listed by using the 'cmemc project list' command.

Options:

- h, --help Show this message and exit.

4.11 Command group: query

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List, execute, get status or open SPARQL queries.

Queries are identified either by a file path, a URI from the query catalog

or a shortened URI (qname, using a default namespace).

In order to get a list of queries from the query catalog, use the list command. One or more queries can be executed one after the other with the execute command. With open command you can jump to the query editor in your browser.

Queries can use a mustache like syntax to specify placeholder for parameter values (e.g. {{resourceUri}}). These parameter values need to be given as well, before the query can be executed (use the -p option).

Options:

-h, --help Show this message and exit.

Commands:

execute	Execute queries which are loaded from files or the query catalog.
list	List available queries from the catalog.
open	Open queries in the editor of the query catalog in your browser.
replay	Re-execute queries from a replay file.
status	Get status information of executed and running queries.

4.11.1 Command: query execute

Usage: cmemc [OPTIONS] QUERIES...

Execute queries which are loaded from files or the query catalog.

Queries are identified either by a file path, a URI from the query catalog, or a shortened URI (qname, using a default namespace).

If multiple queries are executed one after the other, the first failing query stops the whole execution chain.

Limitations: All optional parameters (e.g. accept, base64, ...) are provided for ALL queries in an execution chain. If you need different parameters for each query in a chain, run cmemc multiple times and use the logical operators && and || of your shell instead.

Options:

--accept TEXT	Accept header for the HTTP request(s). Setting this to 'default' means that cmemc uses an appropriate accept header for terminal output (text/csv for tables,
---------------	--

	text/turtle for graphs, * otherwise). Please refer to the Corporate Memory system manual for a list of accepted mime types. [default: default]
--no-imports	Graphs which include other graphs (using owl:imports) will be queried as merged overall-graph. This flag disables this default behaviour. The flag has no effect on update queries.
--base64	Enables base64 encoding of the query parameter for the SPARQL requests (the response is not touched). This can be useful in case there is an aggressive firewall between cmemc and Corporate Memory.
-p, --parameter <TEXT TEXT>...	In case of a parameterized query (placeholders with the '{{key}}' syntax), this option fills all placeholder with a given value before the query is executed. Pairs of placeholder/value need to be given as a tuple 'KEY VALUE'. A key can be used only once.
--limit INTEGER	Override or set the LIMIT in the executed SELECT query. Note that this option will never give you more results than the LIMIT given in the query itself.
--offset INTEGER	Override or set the OFFSET in the executed SELECT query.
--distinct	Override the SELECT query by make the result set DISTINCT.
--timeout INTEGER	Set max execution time for query evaluation (in milliseconds).
-h, --help	Show this message and exit.

4.11.2 Command: query list

```
Usage: cmemc [OPTIONS]
```

List available queries from the catalog.

Outputs a list of query URIs which can be used as reference for the query execute command.

Options:

--id-only Lists only query identifier and no labels or other meta data.

This is useful for piping the ids into other cmemc commands.

-h, --help Show this message and exit.

4.11.3 Command: query open

```
Usage: cmemc [OPTIONS] QUERIES...
```

Open queries in the editor of the query catalog in your browser.

With this command, you can open (remote) queries from the query catalog in the query editor in your browser (e.g. in order to change them). You can also load local query files into the query editor, in order to import them into the query catalog.

The command accepts multiple query URIs or files which results in opening multiple browser tabs.

Options:

-h, --help Show this message and exit.

4.11.4 Command: query status

```
Usage: cmemc [OPTIONS] [QUERY_UUID]
```

Get status information of executed and running queries.

With this command, you can access the latest executed SPARQL queries on the DataPlatform. These queries are identified by UUIDs and listed ordered by starting timestamp.

You can filter queries based on status and runtime in order to investigate slow queries. In addition to that, you can get the details of a specific

query by using the ID as a parameter.

Options:

- id-only Lists only query identifier and no labels or other meta data. This is useful for piping the ids into other cmemc commands.
- raw Outputs raw JSON response of the query status API.
- filter <CHOICE TEXT>... Filter queries based on execution status and time. First parameter CHOICE can be 'slower-than', 'status' or 'type'. The second parameter has to be a finished or running, in case of the 'status' filter, a time in milliseconds in case of the 'slower-than' filter or a query type in case of the 'type' filter.
- h, --help Show this message and exit.

4.11.5 Command: query replay

Usage: cmemc [OPTIONS] REPLAY_FILE

Re-execute queries from a replay file.

This command reads a REPLAY_FILE and re-executes the logged queries. A REPLAY_FILE is a JSON document which is an array of JSON objects with at least a key `queryString` holding the query text OR a key 'iri' holding the IRI of the query in the query catalog. It can be created with the `query status` command, e.g. `query status --raw > replay.json`

The output of this command shows basic query execution statistics.

The queries are executed one after another in the order given in the input REPLAY_FILE. Query placeholders / parameters are ignored. If a query results in an error, the duration is not counted.

The optional output file is the same JSON document which is used as input, but each query object is annotated with an additional 'replays' object, which is an array of JSON objects which hold values for the replay|loop|run IDs, start and end time as well as duration and other data.

Options:

```
--raw           Output the execution statistic as raw JSON.  
--loops INTEGER    Number of loops to run the replay file. [default: 1]  
--wait INTEGER     Number of seconds to wait between query executions.  
                   [default: 0]  
  
--output-file FILE Save the optional output to this file. Input and output  
                   of the command can be the same file. The output is  
                   written at the end of a successful command execution.  
                   The output can be stdout ('-') - in this case, the  
                   execution statistic output is suppressed.  
  
--run-label TEXT   Optional label of this replay run.  
-h, --help         Show this message and exit.
```

4.12 Command group: vocabulary

Usage: cmemc [OPTIONS] COMMAND [ARGS]...

List, (un-)install, import or open vocabs / manage cache.

Options:

```
-h, --help Show this message and exit.
```

Commands:

```
cache      List and update the vocabulary cache.  
import     Import a turtle file as a vocabulary.  
install    Install one or more vocabularies from the catalog.  
list       Output a list of vocabularies.  
open       Open / explore a vocabulary graph in the browser.  
uninstall  Uninstall one or more vocabularies.
```

4.12.1 Command: vocabulary open

Usage: cmemc [OPTIONS] IRI

Open / explore a vocabulary graph in the browser.

Vocabularies are identified by their graph IRI. Installed vocabularies can be listed with the "vocabulary list" command.

Options:

-h, --help Show this message and exit.

4.12.2 Command: vocabulary list

Usage: cmemc [OPTIONS]

Output a list of vocabularies.

Vocabularies are graphs (see 'cmemc graph' command group) which consists of class and property descriptions.

Options:

--id-only Lists only vocabulary identifier (IRIs) and no labels or other meta data. This is useful for piping the ids into other cmemc commands.

--filter [all|installed|installable] Filter list based on status. [default: installed]

--raw Outputs raw JSON.

-h, --help Show this message and exit.

4.12.3 Command: vocabulary install

Usage: cmemc [OPTIONS] [IRIS]...

Install one or more vocabularies from the catalog.

Vocabularies are identified by their graph IRI. Installable vocabularies can be listed with the "vocabulary list --filter installable" command.

Options:

-a, --all Install all vocabularies from the catalog.
-h, --help Show this message and exit.

4.12.4 Command: vocabulary uninstall

```
Usage: cmemc [OPTIONS] [IRIS]...
```

Uninstall one or more vocabularies.

Vocabularies are identified by their graph IRI. Already installed vocabularies can be listed with the "vocabulary list --filter installed" command.

Options:

- a, --all Uninstall all installed vocabularies.
- h, --help Show this message and exit.

4.12.5 Command: vocabulary import

```
Usage: cmemc [OPTIONS] FILE
```

Import a turtle file as a vocabulary.

With this command, you can import a local ontology file as a named graph. and create a corresponding vocabulary catalog entry.

The uploaded ontology file is analysed locally in order to discover the named graph and the prefix declaration. This requires an OWL ontology description which correctly uses the vann:preferredNamespacePrefix and vann:preferredNamespaceUri properties.

Options:

- replace Replace (overwrite) existing vocabulary, if present.
- h, --help Show this message and exit.

4.13 Command group: vocabulary cache

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List and update the vocabulary cache.

Options:

- h, --help Show this message and exit.

Commands:

- list Output the content of the global vocabulary cache.

```
update Reload / updates the data integration cache for a vocabulary.
```

4.13.1 Command: vocabulary cache update

```
Usage: cmemc [OPTIONS] [IRIS]...
```

```
Reload / updates the data integration cache for a vocabulary.
```

```
Options:
```

- a, --all Update cache for all installed vocabularies.
- h, --help Show this message and exit.

4.13.2 Command: vocabulary cache list

```
Usage: cmemc [OPTIONS]
```

```
Output the content of the global vocabulary cache.
```

```
Options:
```

- id-only Lists only vocabulary term identifier (IRIs) and no labels or other meta data. This is useful for piping the ids into other cmemc commands.
- raw Outputs raw JSON.
- h, --help Show this message and exit.

4.14 Command group: workflow

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

```
List, execute, status or open (io) workflows.
```

Workflows are identified by a WORKFLOW_ID. To get a list of existing workflows, execute the list command or use tab-completion. The WORKFLOW_ID is a concatenation of an PROJECT_ID and a TASK_ID, such as "my-project:my-workflow".

```
Options:
```

- h, --help Show this message and exit.

```
Commands:
```

execute	Execute workflow(s).
io	Execute a workflow with file input/output.
list	List available workflow ids.
open	Open a workflow in your browser.
scheduler	List, inspect, enable/disable or open scheduler.
status	Get status information of workflow(s).

4.14.1 Command: workflow execute

Usage: cmemc [OPTIONS] [WORKFLOW_IDS]...

Execute workflow(s).

With this command, you can start one or more workflows at the same time or in a sequence, depending on the result of the predecessor.

Executing a workflow can be done in two ways: Without --wait just sends the starting signal and does not look for the workflow and its result (fire and forget). Starting workflows in this way, starts all given workflows at the same time.

The optional --wait option starts the workflows in the same way, but also polls the status of a workflow until it is finished. In case of an error of a workflow, the next workflow is not started.

Options:

-a, --all	Execute all available workflows.
--wait	Wait until all executed workflows are completed.
--polling-interval INTEGER RANGE	How many seconds to wait between status polls. Status polls are cheap, so a higher polling interval is most likely not needed. [default: 1]
-h, --help	Show this message and exit.

4.14.2 Command: workflow io

Usage: cmemc [OPTIONS] WORKFLOW_ID

Execute a workflow with file input/output.

With this command, you can execute a workflow that uses variable datasets as input, output or for configuration. Use the input parameter to feed data into the workflow. Likewise use output for retrieval of the workflow result. Workflows without a variable dataset will throw an error.

Options:

-i, --input FILE	From which file the input is taken: note that the maximum file size to upload is limited to a server configured value. If the workflow has no defined variable input dataset, this can be ignored.
-o, --output FILE	To which file the result is written to: use '-' in order to output the result to stdout. If the workflow has no defined variable output dataset, this can be ignored. Please note that the io command will not warn you on overwriting existing output files.
--input-mimetype [guess application/xml application/json text/csv]	Which input format should be processed: If not given, cmemc will try to guess the mime type based on the file extension or will fail
--output-mimetype [guess application/xml application/json application/n-triples application/vnd.openxmlformats-officedoc	Which output format should be requested: If not given, cmemc will try to guess the mime type based on the file extension or will fail. In case of an output to stdout, a default mime type will be used (currently xml).
-h, --help	Show this message and exit.

4.14.3 Command: workflow list

Usage: cmemc [OPTIONS]

List available workflow ids.

Options:

```
--raw          Outputs raw JSON objects of workflow task search API response.  
  
--id-only      Lists only workflow identifier and no labels or other meta data. This is useful for piping the IDs into other commands.  
  
--filter <CHOICE TEXT>...  Filter workflows based on project or suitability for the io command .First parameter CHOICE can be 'project' or 'io'. The second parameter has to be a project ID in case of 'project' or 'input-only|output-only|input-output|any' in case of 'io' filter.  
  
-h, --help      Show this message and exit.
```

4.14.4 Command: workflow status

```
Usage: cmemc [OPTIONS] [WORKFLOW_IDS]...
```

Get status information of workflow(s).

Options:

```
--project TEXT          The project, from which you want to list the workflows. Project IDs can be listed with the 'project list' command.  
  
--raw                  Output raw JSON info.  
--filter [Idle|Not executed|Finished|Cancelled|Failed|Successful|Canceling|Running|Waiting]  Show only workflows of a specific status.  
-h, --help              Show this message and exit.
```

4.14.5 Command: workflow open

```
Usage: cmemc [OPTIONS] WORKFLOW_ID
```

Open a workflow in your browser.

Options:

```
-h, --help  Show this message and exit.
```

4.15 Command group: workflow scheduler

```
Usage: cmemc [OPTIONS] COMMAND [ARGS]...
```

List, inspect, enable/disable or open scheduler.

Schedulers execute workflows in specified intervals. They are identified with a SCHEDULERID. To get a list of existing schedulers, execute the list command or use tab-completion.

Options:

```
-h, --help Show this message and exit.
```

Commands:

```
disable  Disable scheduler(s).
enable   Enable scheduler(s).
inspect  Display all meta data of a scheduler.
list     List available scheduler.
open     Open scheduler(s) in the browser.
```

4.15.1 Command: workflow scheduler open

```
Usage: cmemc [OPTIONS] SCHEDULER_IDS...
```

Open scheduler(s) in the browser.

With this command, you can open a scheduler in the workspace in your browser to change it.

The command accepts multiple scheduler IDs which results in opening multiple browser tabs.

Options:

```
--workflow Instead of opening the scheduler page, open the page of the
           scheduled workflow.
```

```
-h, --help Show this message and exit.
```

4.15.2 Command: workflow scheduler list

```
Usage: cmemc [OPTIONS]
```

List available scheduler.

Outputs a table or a list of scheduler IDs which can be used as reference for the scheduler commands.

Options:

- raw Outputs raw JSON.
- id-only Lists only task identifier and no labels or other meta data.
This is useful for piping the IDs into other commands.

-h, --help Show this message and exit.

4.15.3 Command: workflow scheduler inspect

Usage: cmemc [OPTIONS] SCHEDULER_ID

Display all meta data of a scheduler.

Options:

- raw Outputs raw JSON.
- h, --help Show this message and exit.

4.15.4 Command: workflow scheduler disable

Usage: cmemc [OPTIONS] [SCHEDULER_IDS]...

Disable scheduler(s).

The command accepts multiple scheduler IDs which results in disabling them one after the other.

Options:

- a, --all Disable all scheduler.
- h, --help Show this message and exit.

4.15.5 Command: workflow scheduler enable

Usage: cmemc [OPTIONS] [SCHEDULER_IDS]...

Enable scheduler(s).

The command accepts multiple scheduler IDs which results in enabling them one after the other.

Options:

- a, --all Enable all scheduler.
- h, --help Show this message and exit.